



CREST Anti Slip® is an anti-slip treatment for floors, bathrooms, showers and other surfaces. In wet areas they reduce the risk of slips and falls that cause physical damage. Certain kinds of stone cannot be treated to make them anti-slip. These include some kinds of travertine, simulated porcelain and others. Therefore it is important to pretest on one tile to confirm compatibility.

Benefits

- Does not change the appearance of the surface.
- Does not damage the skin on contact.
- Washing and cleaning resistant / Does not degrade easily

Suitable substrates

- Ceramic
- Unsealed stone
- Most hard mineral floor tiles
- Porcelain or enamel bathtubs
- Porcelain hard tile surfaces
- Unsealed concrete & other cementitious hard floor surfaces.

Limitations

- Treated surface must be cleaned/degreased on a regular basis
- This product cannot eliminate the possibility of slipping.
- The great variation between environmental factors, possible surfaces and application techniques, and the lack of control we have over such matters, must affect our policies.

- Always test in small inconspicuous areas before application to the entire surface. If the desired slip-resistant effect is not reached after pretesting on one tile or if there is an objectionable change to the aesthetics of the surface please do not continue.
- If you allow dirt to accumulate over the treated surface, this will diminish the effectiveness of the Treatment.

Packaging

- 1 Gal. (3.78 L) Bottle
- 32 fl. Oz. (946 ml) Bottle

Surface Preparation

Before using CREST Anti Slip ® make sure the surface is clean.

Mixing Procedures

CREST Anti Slip ® is ready to use, simply open the product and apply following the recommended instructions.

Product Application

We highly recommend that you do a pre-test area for compatibility and to establish correct treatment time as described on Treatment label and also as described on previous page before proceeding to apply treatment to the entire job area. This will help to establish the correct length for Treatment time and ensure that you are satisfied with the look and slip resistance of the floor after application to the entire surface.

The use of a slip meter is recommended to help establish the correct treatment time and to ensure a safe reading is achieved in wet conditions before proceeding.

- 1) Lightly moisten the surface.
- 2) Pour CREST Anti Slip® on the wet surface.
- 3) Distribute CREST Anti Slip® on the surface with a sponge or mop
- 4) Allow CREST Anti Slip® to dry for 10 to 15 minutes.
- 5) Rinse the area with clean water to remove material residue.
- 6) There is no curing time. The floor can be put back into use immediately once the clean water rinses have been completed.

Cleanup

Clean tools and hands with soap and water immediately after use

Protection

May be harmful or fatal if swallowed. May irritate eyes and skin. This product is combustible and contains petroleum distillates. Use in ventilated areas. Use vapor mask, gloves, goggles and appropriate clothing. Avoid exposure to high concentrations of vapors.

Clean your hands after using the product avoid eye contact or prolonged contact with the skin, if eye contact occurs, rinse with water for 15 minutes and consult a physician immediately.

Keep children and pets away from the area until the material is completely dry. Keep in the original container tightly closed.

Emergency Procedure and First Aid

If swallowed:

Do not induce vomiting. Drink water and call a physician immediately.

If contact with skin and eyes occur:

Rinse with water for at least 15 minutes. If irritation persists consult your physician.

IMPORTANT

We are not responsible for any loss or damage caused due to the application of this product. Prior to application, the user must confirm whether the product is suitable for their intended use. The user must assume responsibility for the risks or damages arising from an application other than specified.

Summary Technical Chart

Packaging:	5 Gal. Pail (19 lt.) , 32 fl. Oz. Bottle (946 ml)
Shelf Life:	12 months in a dry cool area, in the original packaging and unopened.
Duration:	2 - 3 years
Use:	Interior and Exterior
Coverage:	Typical coverage is 400 sq. ft. / gallon.
Dry Time:	1 - 2 hours

*Values might vary depending on the tile size, leveling the substrate, conditions and method of installation.

Note:

Average values obtained at 73°F ± 4°F and relative humidity of 50 ± 5%. Performance may vary depending on the format and size of the trowel to use as the leveling of the substrate.

CREST ANTI SLIP

Anti-slip treatment for floors, bathrooms, showers and other surfaces.

For ceramic and porcelain tiles, among other surfaces.

*Monterrey and Mexico plants Certified.

Technical Information

For technical support and assistance, please visit our website at www.crest.com.mx

For questions or comments contact technicalservice@crest.com.mx

**Crest Headquarters**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (81) 8047-5000

**Monterrey Plant**

Carretera a Saltillo km. 339.5
Santa Catarina, N.L. C.P. 66350
Tel. (81) 8220-5050

**Mexico City Office**

Mariano Escobedo No. 525
3er piso Rincón del Bosque
México, CDMX C.P. 11580
Tel. (55) 5255-0355

**Tizayuca Plant**

Camino a Huitzila s/n
Zona Industrial
Tizayuca, Hgo. C.P. 43804
**Tels. (779) 796-3873
796-3872 and 800-715-7618**

**Guadalajara Plant**

Calle 1 No. 665 esquina Calle 26
Zona Industrial
Guadalajara, Jal. C.P. 44940
Tel. (33) 3134-5600

**Chihuahua Plant**

Privada Santa Rosa No. 3
Zona Industrial Nombre de Dios
Chihuahua, Chih. C.P. 31110
Tel. (614) 424-1420

**Morelia Plant**

Libramiento Norte No. 1061
Col. El Realito
Morelia, Mich. C.P. 58116
**Tel. (443) 327-3653
and 327-3590**

**Guatemala Plant**

24 Calle Final 26-70 "A"
Zona 12, Anastasio Tzul
Tel. +502 2222-2333

**Durango Plant**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (871) 689-0891

**Cancún Warehouse**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (998) 882-2125

**Chile Plant**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. +56 (2) 2387-4200