

# Crest Ultramax Caulk



**CREST**  
PREMIUM TILE SETTING SOLUTIONS



**CREST CAULK® Ready to use, flexible organic seal adhesive, latex based, specially designed as a flexible seal adhesive for interior installations of most common household surfaces and types of impervious, vitreous, semi and non-vitreous tiles such as porcelain, ceramic and natural stone on floors, walls, sinks, showers and countertops.**

## Benefits

- Excellent adhesion.
- Great flexibility.
- Restores cracks or worm grout joints.
- Ready to use.
- Easy to apply.
- Smooth and creamy consistency.
- Residential and commercial use.
- Water Clean up.
- VOC Compliant.

## Suitable Tile Types

- Around tubs
- Showers
- Sinks
- Bonds bath fixtures
- Loose tiles

## Limitations

- Install only at temperatures between 50°F and 100°F (10°C and 38°C).
- Maximum joint width and depth should not exceed 1/4" (6 mm).
- Not suggested for use on aquariums.
- Not suggested for use in areas with constant water exposure.

- Do not use to install grab bars.
- Protect from rain and exposure to water for 24 hrs.
- Allow new concrete to cure 30 days before caulking.
- Do not attempt to thin caulk.
- Do not use for joints subject to heavy abrasion or wear.
- Allow a minimum of 4 to 6 hours drying time before painting. • For interior use only.

## Packaging

- 10.5 oz. (310 ml) cartridge.

## Surface Preparation

Before applying CREST CAULK® it is necessary to clean the surface and joints, which must be structurally sound, dimensionally stable, perfectly leveled and clean, free from oil, paint, sealers, wax, dirt or any other type of impurity that might prevent proper adhesion. Concrete must be cured 28 days and accept water penetration. Concrete must be free of efflorescence and not subject to hydrostatic pressure. Concrete slabs should have a coarse finish to enhance the bond. Expansion joints should never be bridged with setting material. Do not sand flooring materials containing asbestos. Install at ambient temperature, should be maintained above 50° F (10°C) or below 100°F (38°C) for 72 hours to achieve proper bond.

## Mixing Procedures

CREST ULTRAMAX CAULK® is ready to use, simply open the product and apply. No mixing is required.

## Product Application

- 1) Clip off tip of spout at a 45° angle to desired size.
- 2) Load cartridge into caulking gun and apply using steady, even pressure to completely bridge joints.
- 3) Smooth caulk using wet finger or a damp cloth for a neat appearance.
- 4) Wipe away excess with a damp cloth before surface skins over.
- 5) After grouting the installation is necessary to wait 24 hours before allowing foot traffic. If the temperature is below 50°F, wait 48 hours.
- 6) Protect from water until cured (24 hrs.). May be painted over in 4-6 hours depending on climatic conditions. Larger beads may require longer drying time.
- 7) For installations that require higher impact ratings and resistance to chemicals and stain, use EpoxyCREST 2020, 100% solids epoxy grout sanded, available in 5 colors. In facilities that are subject to structural micro movements, thermal shock or vibration is suggested the use of flexible joints systems, such as CREST FLEXIGROUT®.

## Curing

Minimum of 24 hrs. before exposure to water is suggested. Temperature and humidity can affect working time and setting time.

## Cleanup

Clean your skin, tools and tile work with warm water and mild soap while the material is not dry.

## Storage

Store in a cool dry area.

## Protection

Clean your hands after using the product, avoid eye contact, or prolonged contact with the skin, if eye contact occurs, rinse with water for 15 minutes and consult a physician immediately.  
Keep out of the reach of children.

## IMPORTANT

**We are not responsible for any loss or damage caused due to the application of this product. Prior to application, the user must confirm whether the product is suitable for their intended use. The user must assume responsibility for the risks or damages arising from an application other than specified.**

## Summary Technical Chart

<b>Available:</b>	White and Cream
<b>Packaging:</b>	10.1 oz. (300 ml ) Cartridge
<b>Shelf Life:</b>	12 months in a cool dry area, in original packing and unopened.
<b>Tack Free Time</b>	< 60 Minutes
<b>Installation Temperature:</b>	Between 50/100°F (10/38°C)
<b>pH:</b>	7 to 10
<b>Flash Point:</b>	> 200 F°
<b>Tooling:</b>	Excellent
<b>Paintability:</b>	Excellent @ 4-6 hrs. drying
<b>Crack Resistance:</b>	Excellent
<b>Slump:</b>	< 0.15 mm
<b>Shrinkage:</b>	Excellent
<b>Stain Resistant:</b>	Excellent
<b>Test for mold growth:</b>	Does not support mold growth
<b>Installations:</b>	Interior and/ or exterior

\*Values might vary depending on the tile size, leveling the substrate, conditions and method of installation.

## Approximate Product Coverage

Size	Average Coverage
10.1 oz. (300 ml)	24 lineal ft. (7.3 m) ¼" x ¼" joint

### Note:

Average values obtained at 73°F ± 4°F and relative humidity of 50 ± 5%. Performance may vary depending on the format and size of the trowel to use as the leveling of the substrate.

**ULTRAMAX CAULK**

Flexible organic seal, latex based

For walls and floors interiors

Porcelain, glass, mosaics, ceramic tiles and natural stones

\*Monterrey and Mexico plants Certified.

**Technical Information**For technical support and assistance, please visit our website at [www.crest.com.mx](http://www.crest.com.mx)For questions or comments contact [technicalservice@crest.com.mx](mailto:technicalservice@crest.com.mx)**Crest Headquarters**

Av. Pedro Ramírez Vázquez #200-1  
Col. Del Valle Oriente  
San Pedro Garza García,  
Nuevo León. C.P. 66260  
Tel. (81) 8047-5000

**Monterrey Plant**

Carretera a Saltillo km. 339.5  
Santa Catarina, N.L. C.P. 66350  
Tel. (81) 8220-5050

**Mexico City Office**

Mariano Escobedo No. 525  
3er piso Rincón del Bosque  
México, CDMX C.P. 11580  
Tel. (55) 5255-0355

**Tizayuca Plant**

Camino a Huitzila s/n  
Zona Industrial  
Tizayuca, Hgo. C.P. 43804  
Tels. (779) 796-3873  
796-3872 and 800-715-7618

**Guadalajara Plant**

Calle 1 No. 665 esquina Calle 26  
Zona Industrial  
Guadalajara, Jal. C.P. 44940  
Tel. (33) 3134-5600

**Chihuahua Plant**

Privada Santa Rosa No. 3  
Zona Industrial Nombre de Dios  
Chihuahua, Chih. C.P. 31110  
Tel. (614) 424-1420

**Morelia Plant**

Libramiento Norte No. 1061  
Col. El Realito  
Morelia, Mich. C.P. 58116  
Tel. (443) 327-3653  
and 327-3590

**Guatemala Plant**

24 Calle Final 26-70 "A"  
Zona 12, Anastasio Tzul  
Tel. +502 2222-2333

**Durango Plant**

Av. Pedro Ramírez Vázquez #200-1  
Col. Del Valle Oriente  
San Pedro Garza García,  
Nuevo León. C.P. 66260  
Tel. (871) 689-0891

**Cancún Warehouse**

Av. Pedro Ramírez Vázquez #200-1  
Col. Del Valle Oriente  
San Pedro Garza García,  
Nuevo León. C.P. 66260  
Tel. (998) 882-2125

**Chile Plant**

Av. Pedro Ramírez Vázquez #200-1  
Col. Del Valle Oriente  
San Pedro Garza García,  
Nuevo León. C.P. 66260  
Tel. +56 (2) 2387-4200