

Crestucco Master Primer



CREST STUCCO PRIMER is an acrylic latex resins based, ready to use, specially made to be applied over the any basecoat, reducing the appearance of efflorescence due to the product containing cement implicated in the system. Enhance and improves the consistency of the finish coat and the coverage, increase water resistance and compressive impacts.

Benefits

- Excellent to improve the performance of your CREST STUCCO SYSTEM
- Increase water resistance of the STUCCO SYSTEM
- Enhance STUCCO TOP COATS colors
- Great sealing properties over most all basecoats
- Improves freeze/thaw durability
- Low odor
- Inhibits efflorescence

Suitable Substrates

- Basecoat
- Concrete
- Cement plasters
- Cement backer board
- Cement mortar beds
- Concrete masonry, bricks
- Gypsum walls

Limitations

- Install only at temperatures between 50°F and 100°F (10°C and 38°C).
- Do not use over dimensionally unstable substrates such as hardwood flooring, oriented strand board (OSB), substrates containing asbestos, or metal. See "Suitable Substrates" section above.

- Not recommended for installations subject to prolonged water immersion, ponds, or in areas subject to hydrostatic pressure
- Do not use cleaning solvents.
- The substrate must be fully cured, dry, free of alkalis and moisture.
- Temperature must be greater or equal to 4°C during the application and drying process. If necessary, additional heat and protection will be provided against precipitation.
- Use only on surfaces in good condition, clean, dry and free of any debris that may affect proper adhesion of the product to the surface.
- Before application of CREST STUCCO ACRYLIC, always properly prepare the surface and prime with CREST STUCCO PRIMER.

Packaging

- 5 gal. Pail

Surface Preparation

Before using CREST STUCCO PRIMER it is necessary to clean the surface, must be dry and free from oil, waxes, grease, sealers, finishes, paint or any other type of impurity.

Use appropriate safety equipment as chemical resistant gloves when handling this product.

Mixing Procedures

- CREST STUCCO PRIMER is ready to use, simply open the product and apply following the recommended instructions.
- Note. Do not add more additive or water, otherwise the properties of the CREST STUCCO PRIMER could be adversely affected.

Important:

Do not mix more material than you can apply in 2 hours since the material began to set in bucket.

Product Application

Make sure the surface is clean, dry and free of wax, grease and paint.

- Stir until a mixture of homogeneous consistency, using a mechanical mixer.
- The application may be made by brush, roller or spray.
- Finally, CREST STUCCO PRIMER must be completely dry before placing a Top coat over (drying time of the primer 30 -45 min).

Cleanup

Clean tools and tile work with water before the material hardens. Cured material must be mechanically removed.

Storage

Store in a cool dry area.

Protection

Clean your hands after using the product, avoid eye contact, or prolonged contact with the skin, if eye contact occurs, rinse with water for 15 minutes and consult a physician immediately.x

Keep out of the reach of children.

IMPORTANT

We are not responsible for any loss or damage caused due to the application of this product. Prior to application, the user must confirm whether the product is suitable for their intended use. The user must assume responsibility for the risks or damages arising from an application other than specified.

Summary Technical Chart

Packaging:	5 Gal. Pail (19 lt.)
Aroma:	Low odor
Color:	White
Shelf Life:	12 months in a cool dry area, in original packing and unopened.
Emulsion Type:	Acrylic Emulsion
Use:	Interior and Exterior
Coverage:	1600 – 1900 sq. ft. (150 – 180 m ²) per pail
Dry time:	30 – 45 Minutes

*Values might vary depending on the tile size, leveling the substrate, conditions and method of installation.

Specifications

Test Method	Requirements	Test Results
Viscosity	ATSM D 2196	10,000 ± 2,000
pH at 25°C	ASTM E 70	9.5 ± 1.0
Solids Weight %	ASTM D 2369	70.0 ± 2.0
Density	ASTM D 70	1.60 ± 0.20

Note:

Average values obtained at 73°F ± 4°F and relative humidity of 50 ± 5%. Performance may vary depending on the format and size of the trowel to use as the leveling of the substrate.

CREST STUCCO PRIMER

Acrylic Latex liquid primer

Crest Stucco System, for interiors or exteriors

*Monterrey and Mexico plants Certified.

Technical InformationFor technical support and assistance, please visit our website at www.crest.com.mxFor questions or comments contact customerservice@crest.com.mx**Crest Headquarters**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (81) 8047-5000

**Monterrey Plant**

Carretera a Saltillo km. 339.5
Santa Catarina, N.L. C.P. 66350
Tel. (81) 8220-5050

**Mexico City Office**

Mariano Escobedo No. 525
3er piso Rincón del Bosque
México, CDMX C.P. 11580
Tel. (55) 5255-0355

**Tizayuca Plant**

Camino a Huitzila s/n
Zona Industrial
Tizayuca, Hgo. C.P. 43804
Tels. (779) 796-3873
796-3872 and 800-715-7618

**Guadalajara Plant**

Calle 1 No. 665 esquina Calle 26
Zona Industrial
Guadalajara, Jal. C.P. 44940
Tel. (33) 3134-5600

**Chihuahua Plant**

Privada Santa Rosa No. 3
Zona Industrial Nombre de Dios
Chihuahua, Chih. C.P. 31110
Tel. (614) 424-1420

**Morelia Plant**

Libramiento Norte No. 1061
Col. El Realito
Morelia, Mich. C.P. 58116
Tel. (443) 327-3653
and 327-3590

**Guatemala Plant**

24 Calle Final 26-70 "A"
Zona 12, Anastasio Tzul
Tel. +502 2222-2333

**Durango Plant**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (871) 689-0891

**Cancún Warehouse**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. (998) 882-2125

**Chile Plant**

Av. Pedro Ramírez Vázquez #200-1
Col. Del Valle Oriente
San Pedro Garza García,
Nuevo León. C.P. 66260
Tel. +56 (2) 2387-4200